



TECHNICAL DATA

GB 4S SUPER 10W-40

APPLICATIONS

GB 4S SUPER 10W-40 is a semi-synthetic 4-stroke motorcycle engine oil that has been developed using the highest quality synthetic and virgin base oils and enhanced additive systems, for use in all high performance 4-stroke European and Japanese motorcycle engines, including multi-cylinder, multi-valve, v-twin air- or water-cooled sports models. It is suitable for use in motorcycles with oil-immersed clutches.

PERFORMANCE FEATURES

GB 4S SUPER 10W-40 offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability
- Exceptional shear stability
- Excellent gear shift quality
- Excellent wet clutch performance

PERFORMANCE DETAILS

GB 4S SUPER 10W-40 may be used where the following specifications are required:

API SH

JASO MA

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312

Fax: 0191 477 9544

e-mail: gblsales@gb-lubricants-fuels.co.uk

www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			10W-40
Appearance	-	-	Clear amber liquid
Kinematic Viscosity @ 100°C	cSt	-	14.4
Kinematic Viscosity @ 40°C	cSt	-	99.5
Viscosity Index	-	-	149
Density	kg/m ³	-	874
CCS @ -25°C	cP	-	6530
HTHS @ 150°C	mPa.s	-	3.89
Noack	%	-	12.6
KO AftVisc	cSt	-	13.72
KO % ShLoss	%	-	4.62
L38 AftVisc	cSt	-	-
L38 % ShLoss	%	-	4.77
Flash Point	°C	IP 34	210

STORAGE AND HANDLING

GB 4S SUPER 10W-40 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB 4S SUPER 10W-40 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.