



TECHNICAL DATA

GB TURBO SX 5W-30

APPLICATIONS

GB TURBO SX 5W-30 is a fully synthetic passenger car oil formulated using the highest quality synthetic base oils and enhanced additive systems for use in both petrol and diesel engines. It has been specifically engineered for all Ford cars and vans requiring a product meeting Ford WSS-M2C-913-B and, because of its lower viscosity, it is recognised as a fuel-efficient lubricant which also provides better cold starting and less wear on engines, starter motors and batteries. Although specifically engineered for Ford it may also be used in vehicles manufactured by other OEMs when the performance and viscosity grades are applicable.

PERFORMANCE FEATURES

GB TURBO SX 5W-30 has been developed for Ford cars and vans and also as a fuel-efficient lubricant and offers the following features:

- Improved engine wear protection
- Rust and corrosion protection
- Excellent piston deposit control
- Excellent oxidation stability
- Improved fuel economy
- Exceptional shear stability

PERFORMANCE DETAILS

GB TURBO SX 5W-30 may be used where the following specifications are required:

ACEA A1/B1 API SL	FORD WSS-M2C913-B ILSAC GF-3
----------------------	---------------------------------

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP

Tel: 0191 490 4312
Fax: 0191 477 9544
e-mail: gblsales@gb-lubricants-fuels.co.uk
www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

GB LUBRICANTS

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
SAE			5W-30
Appearance	-	-	Clear amber liquid
Kinematic Viscosity @ 100°C	cSt	IP 71	10.0
Kinematic Viscosity @ 40°C	cSt	IP 71	57.8
Viscosity Index	-	IP 226	161
Density	kg/m ³	IP 160	850
CCS @ -30°C	cP	ASTM D 5293	3660
HTHS Viscosity	mPa.s	CEC L-36-A-97	2.9
MRV TP-I @ -35°C	cP	ASTM D 4684	16000
Yield Stress	Pa	-	None
Noack	%	CEC L-40-A-93	13.0
Total Base Number	mg KOH/g	ASTM D 2896	8.8
Sulphated Ash	% mass	ASTM D 874	1.1
Flash Point	°C	IP 34	188
Pour Point	°C	IP 15	-45

STORAGE AND HANDLING

GB TURBO SX 5W-30 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB TURBO SX 5W-30 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.