



TECHNICAL DATA

GB UNICUT® 3

A light coloured, extreme pressure neat cutting oil

APPLICATIONS

GB UNICUT® 3 is a light coloured, medium viscosity cutting oil based on the highest quality mineral virgin base oils. It is suitable for machining operations on both medium tensile steels and yellow metals, such as brass and copper, and is ideally suited for operations on automatic machines.

PERFORMANCE FEATURES

Special features of GB UNICUT® 3 are:

- Its high quality mineral virgin basestock
- It contains a non-corrosive chlorinated extreme pressure additive
- The use of a synthetic ester type additive, to impart good lubricity
- It is non-staining towards yellow metals
- Its light colour and pleasant odour

CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Light amber
Kinematic Viscosity @ 40°C	cSt	IP 71	17.9
Density @ 15°C	kg/m ³	IP 160	876
Flash Point	°C	IP 34	200

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gbsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB UNICUT® 3 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB UNICUT® 3 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.