



# TECHNICAL DATA

## GB UNICUT® 7

A medium viscosity cutting oil, incorporating an inactive sulphurised fatty ester

### APPLICATIONS

GB UNICUT® 7 is a medium viscosity cutting oil containing lubricity additives, together with a very low corrosivity extreme pressure sulphurised ester. The cutting oil is classified as inactive and can be used for operations on cuprous and aluminium alloys and for a wide variety of general purpose cutting.

### PERFORMANCE FEATURES

Special features of GB UNICUT® 7 are:

- Its high quality mineral virgin basestock
- Its medium viscosity
- Its high lubricity level
- The use of an inactive sulphurised fatty ester
- Its possible use as a combined general purpose cutting oil AND slideway lubricating oil

### CHARACTERISTICS

TEST	UNIT	METHOD	TYPICAL PHYSICAL CHARACTERISTICS
Appearance			Medium amber
Kinematic Viscosity @ 40°C	cSt	IP 71	33.9
Density @15°C	kg/m <sup>3</sup>	IP 160	878
Flash Point	°C	IP 34	205

Cont'd .../...

## **GB LUBRICANTS**

Albany Road Gateshead NE8 3BP  
 Tel: 0191 490 4312  
 Fax: 0191 477 9544  
 e-mail: gblsales@gb-lubricants-fuels.co.uk  
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093  
ISO 9001



EMS 72776  
ISO 14001



OHS 88475  
OHSAS 18001

## **STORAGE AND HANDLING**

GB UNICUT® 7 should be stored under cover to avoid water collecting in the rim of upturned barrels.

## **HEALTH, SAFETY AND THE ENVIRONMENT**

GB UNICUT® 7 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, [www.environment-agency.gov.uk](http://www.environment-agency.gov.uk), as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.