



TECHNICAL DATA

GB UNICUT® 8

A high lubricity cutting oil, incorporating chlorinated extreme pressure additives

APPLICATIONS

GB UNICUT® 8 is a medium viscosity cutting oil, containing both lubricity and chlorinated extreme pressure additives. It can be used for broaching, tapping and threading operations on alloy, high tensile and stainless steels.

PERFORMANCE FEATURES

Special features of GB UNICUT® 8 are:

- Its high quality mineral virgin basestock
- Its medium viscosity
- Its high lubricity level
- The high level of non-corrosive chlorinated extreme pressure additives
- It is non-staining towards yellow metals such as brass and copper

CHARACTERISTICS

| TEST | UNIT | METHOD | TYPICAL PHYSICAL CHARACTERISTICS |
|----------------------------|-------------------|--------|----------------------------------|
| Appearance | | | Amber |
| Kinematic Viscosity @ 40°C | cSt | IP 71 | 16.9 |
| Density @ 15°C | kg/m ³ | IP 160 | 926 |
| Flash Point | °C | IP 34 | 200 |

Cont'd .../...

GB LUBRICANTS

Albany Road Gateshead NE8 3BP
 Tel: 0191 490 4312
 Fax: 0191 477 9544
 e-mail: gbsales@gb-lubricants-fuels.co.uk
 www.gb-lubricants-fuels.co.uk

A division of Goodall Bates & Todd Ltd



Q 06093
ISO 9001



EMS 72776
ISO 14001



OHS 88475
OHSAS 18001

STORAGE AND HANDLING

GB UNICUT® 8 should be stored under cover to avoid water collecting in the rim of upturned barrels.

HEALTH, SAFETY AND THE ENVIRONMENT

GB UNICUT® 8 is not classified as hazardous under current UK Health & Safety and Environmental Legislation when used in the application for which it is intended.

For guidance on storage and handling of all lubricants and related products, GB Lubricants recommend the Environment Agency, www.environment-agency.gov.uk, as an excellent source of advice.

If you have any queries, please do not hesitate to contact either your local Technical Sales Representative or our Technical Department.

The Company policy is to ensure that a range of products is supplied which complies with the latest specifications and codes within the relevant industry. As part of this development process, we therefore reserve the right to amend formulations and specifications, without prior notice.